3 **REVISIONS NOTES:** REV. DESCRIPTION DRAWN BY CHECKED BY DATE DIMENSIONS IN BRACKETS, [], ARE MILLIMETERS AND FOR REFERENCE ONLY INITIAL RELEASE C WALKER 1/10/2025 RECOMMENDED MOUNTING HARDWARE: 1/2" [M12] THREADED ROD WITH SERRATED FLANGE NUTS D D 660.40 26.00 **DIMENSION AA** MODEL NO. DROP DISTANCE DL3B-7.5 6 3/4" [172] 7' 11" [2.41m] 4X ∅.625 DL3B-9.5 7 3/4" [197] 9' 6" [2.90m] -MOUNTING HOLES DL3B-11 SEE NOTE 2 8 3/4" [222] 11' [3.35m] 2895 DL3B-12.5 9 3/4" [248] 12' 6" [3.81m] 114.0 MAX. DROP DIST. DL3B-14 10 3/4" [273] 14' [4.27m] 196.85 7.75 727.08 28.63 UNLESS OTHERWISE SPECIFIED: DRAWN BY **DISPLAY DEVICES** DIMENSIONS ARE IN INCHES C WALKER TOLERANCES: Design · Engineering · Manufacturing MATERIAL $.XX = \pm .020$.XXX = \pm .010 TITLE: $.XXXX = \pm .0050$ ANGLE: ± .5° INTERPRET DRAWING PER Y14.100. SAMPLE DL3B - 9.5 DIMENSIONS AND TOLERANCES PROPRIETARY AND CONFIDENTIAL ARE IN ACCORDANCE WITH ASME Y14.5 - 2009. THE INFORMATION CONTAINED IN THIS THIRD ANGLE PROJECTION DRAWING IS THE SOLE PROPERTY OF SIZE DWG. NO. REV DISPLAY DEVICES, INC. ANY REPRODUCTION IN PART OR AS A WHOLE SAMPLE DL3B LIFT WITHOUT THE WRITTEN PERMISSION OF DISPLAY DEVICES, INC IS PROHIBITED. SCALE: 1:16 SHEET 1 OF 1 DO NOT SCALE DRAWING 3 2